



# AQUALITY

AQUALITY IB WG – AQUALITY IB – AQUALITY WG

Sparkling Water Bottled & POU Water Cooler

## Specifications

Code	Description	Hourly (Ltrs)	Instant Draw Off (Ltrs)	Ice Bank (POU) / Bottled	Ambient Water	Chilled Water	CO <sup>2</sup> Sparking Water	Requires Gas	KLARAN UVC LED Water Purification System	Weight	Dimensions H x W x D mm
CEAQ28PWG	AQUALITY IB WG	28ltr/h	5ltr	POU	✓	✓	✓	✓	✓	20kg	1120 x 334 x 330
CEAQ20P	AQUALITY IB	20ltr/h	3ltr	POU	✓	✓	-	-	✓	20kg	1120 x 334 x 330
CEAQ22BWG	AQUALITY WG	22ltr/h	5ltr	BOTTLED	✓	✓	✓	✓	-	20kg	1120 x 334 x 330 (+ Bottle)

## Description

- **AQUALITY IB WG Ice Bank POU Cooler with CO<sup>2</sup> FIZZ**, supplies Chilled & Ambient Water plus Chilled Sparkling Water.
- **AQUALITY IB Ice Bank POU Cooler** supplies Chilled & Ambient Water.
- **AQUALITY WG Bottled Cooler with CO<sup>2</sup> FIZZ** supplies Chilled & Ambient Water plus Chilled Sparkling Water.

- The AQUALITY range is elegant in design and sturdily built.
- The 1ltr carbonator capacity on WG models allows for a constant output of cups of Chilled Sparkling Water. Carbonated Coolers require a Gas Regulator to connect to the CO<sup>2</sup> Cylinder.
- Imbedding the Carbonation Unit in the Ice Bank Chiller ensures lasting and excellent carbonation.
- The Ice Bank chilling system ensures a constant chilled temperature of less than 10°C, even at a high incoming water temperature of 20°C and a room temperature of 25°C. (When installing an Ice Bank Cooler, please ensure that the Ice Bank is filled with water before turning the Cooler on. Without water, the Chilling unit will burn out).
- All AQUALITY models come with an integrated Cup Dispenser.
- WRAS Approved.
- The KLARAN UVC LED can be retrofitted to the AQUALITY IB Coolers. The KLARAN Processor sits between the Ice Bank Tank and the Dispensing Tap. As the Water passes through, on its way to the Tap, the UVC LED Radiation of the KLARAN destroys Bacteria and Viruses in the Drinking Water. KLARAN UVC LED, once installed, requires virtually no servicing.

## Accessories



The KLARAN UVC LED Shield creates UVC LED radiation which destroys Bacteria and Viruses in the Drinking Water, as it passes through the Shield on its way from the Ice Bank Tank to the Tap. Once installed, the UVC LED Shield is virtually service free (factory-installed).



Carbonated coolers require a gas regulator to connect the CO<sup>2</sup> cylinder. Our REGCO2 gas regulator is suitable for 600gm disposable CO<sup>2</sup> cylinders.



POU Installation rail with filter. Includes compression fitting, 1-Micron green filter, water block, copper pressure reducing valve & non-return valve.

**AA FIRST**  
WATER COOLERS  
& BOILERS



**Quality - Reliability - Integrity**