

# ArcticChill 98CL

Direct Chill Cooler Plus Contactless Dispensing To Avoid Hand To Tap Contamination

- Chiller capacity: 30 - 40 ltrs of below 12°C chilled water/hour
- Copious amounts of ambient water
- Can be fitted with drip tray overflow kits & mains drainage
- Fits our standard cowl and wall bracket
- FloodGuard inlet solenoid protects the cooler against large scale flooding
- Impressive 23cm dispensing height
- Fitted with contactless dispensing

## Contactless Dispensing

- An infra red sensor activates dispensing when you place your hand approximately 4cm over the sensor



The ArcticChill 98  
Delivers 30 - 40 ltrs of  
Below 12°C Chilled  
Water Per Hour &  
Copious Amounts Of  
Ambient Water

Place Your Hand Over The  
Sensor <4cm

23cm Dispensing  
Height To Fill  
Bottles

**AA** FIRST  
WATER COOLERS  
& BOILERS



Quality – Reliability – Integrity

# ArcticChill 98CL

Direct Chill Cooler Plus Contactless Dispensing To Avoid Hand To Tap Contamination



## Key Feature

First select ambient or cold, then hold the dispensing button down



(Infra Red Sensors)

## ArcticChill 98CL Infra Red Sensor Enables Contactless Dispensing

- Green power LED indicates power is on
- Orange LED will light up during dispensing
- For contactless dispensing place your hand approx. 4cm over the ambient or chilled sensor on top of the cooler



## Accessories For The ArcticChill 98

Installation rail with filter. Includes compression fitting, 1-Micron green filter, water block, copper pressure reducing valve & non-return valve



FloodGuard - closed inlet solenoid only opens to allow water into the cooler, when water is dispensed. By remaining closed all other times it protects the cooler against leaks



Filter housing with carbon block candle & nanofilter



Mains drainage - connect the drip tray to mains drainage. Can be supplied with a pump, to pump the water over 50m & a rise of 5m



Cowling to fix the cooler securely to the wall. (Supplied separately)



10 litre overflow system with alarm to signal when full. (Factory fitted)



3 Litre overflow kit connects the drip tray to a 3 litre alarmed overflow container. The container has a tap to empty without removing it



A pumped main drainage system pumps the waste water from the drip tray over a distance of 100m & a rise of 5m. (Factory installed)



Description	Hourly Output		Temp	Dimensions H X W X D (mm)	Weight (Kg)
	Chilled	Ambient			
POU Floor Standing	30-40 Ltrs/Hr	Indefinite	Below 12C	1135 x 340 x 340	25

**AA**FIRST  
WATER COOLERS  
& BOILERS

[www.aafirst.co.uk](http://www.aafirst.co.uk)