


The AA First 3ltr Aquality Overflow CEAQOVERFLOW Operating Instructions

If the alarm sounds, empty the bottle.

- Disconnect the cooler from the electrics
- Remove the lower side panel of the Aquality by rotating the lock (1) .
- Separate the overflow water pipe from the overflow container •
- Remove the overflow container and empty (2) •
- Re-assemble the cooler in reverse order .





The alarm will silence once the overflow container has been emptied. Alternatively, you can switch it off manually using the switch attached to the overflow container.

*Please remember to switch the alarm back on once you have finished re-installing it.





We recommend the use of chlorine tablets in the bottle to help prevent smells.

We recommend customers empty the bottles on a frequent basis, to avoid the alarm sounding.

We recommend that customers check the alarm battery and replace it if exhausted.

AA First is a division of Circon Ltd: Registered in England 5121722 European HQ: French HQ:

Cedar House T: + 44 (0) 1635 202489 Grange Farm E: enquiries@aafirst.co.uk Long Lane Newbury RG14 2TF W: aafirst.co.uk

W: aafirst.eu

 T: +33 (0) 674437445
 T: +33 (0) 640650708

 E: derek@aafirst.eu
 E: lesley@aafirst.eu

 W: aafirst.fr
 W: aafirst.fr

 W: aafirst.de
 W: aafirst.de

W: aafirst.eu

